Operation Instructions

A22 1st Year Tune-up Kit (1.6, 115V) R8-020009-000

- 1. Using the instructions in the maintenance section of the A22 Service Manual, p/n 14-900077-000 (included), completely drain the Cleaner Supply Tank. (Section 5, page 102)
- 2. With the machine in the operating position, remove and replace the following items from the Cleaning System:
 - a. 1 each 11-655044-004 Cleaner Filter Screen Only (page 103)
 - b. 1 each 11-655037-000 Cleaner Vent Filter (top of cleaner tank) AND, 1 each 11-655038-000 Cleaner Vent Check Valve (item 2, page 16)
 - c. 1 each 14-100487-000 Waste Tank Foam Seal "D" Shape (page 106)
 - d. 1 each Vacuum Hose Assembly, consisting of 1 each 11-655034-000 vacuum hose (24"), 1 each 11-655035-000 Grey Hose Cuff, and 1 each 11-603204-000 Hose Clamp. (item 3, page 17)
- 3. Remove and disconnect the vacuum motor. Replace the following items:
 - a. 2 each 14-100606-120 Vacuum Motor Replacement Brushes 120V
 - b. 1 each 14-100607-000 Vacuum Motor Housing

Replace and reconnect the vacuum motor.

- 4. Using the instructions in the maintenance section of the A22 Service Manual p/n 14-900077-000 (included), completely drain the Conditioner Supply Tank (Section 5, starting on page 107)
- 5. With the machine in the operating position, remove and replace the following items from the Conditioning System:
 - a. 1 each 11-655029-001 Conditioner Filter, Spin-On (page 109)
 - b. 1 each 11-655024-004 Conditioner Filter Screen Only (page 110)
- 6. Stand the machine up into the transport position to replace the following items:
 - a. 2 each 11-616025-000 Duster Up/Down Switches (page 92)
 - b. 2 each 11-695010-000 Dual Caster Wheels (item 8, page 23)
 - c. 5 each 11-655002-000 Check Valve Strainer AND, 5 each 11-655003-000 Cleaner Spray Nozzle
 - d. 1 each 14-100374-000 Squeegee Clamp Foam AND, 1 each 14-100320-000 Foam Absorbent Wiper (page 97) at the same time replace "d" (next)
 - e. 1 each 14-100126-000 Urethane Squeegee Blade (page 98)
 - f. 1 each 14-100378-000 Vacuum Diffuser Foam (Vacuum Exhaust)
 - g. 1 each 14-100390-000 Middle Frame Foam (item 10, page 79)

Kit Consists

PART NUMBER	DESCRIPTION	QTY
11655044004	FILTER- SCREEN ONLY, CYL.50x250M	1
11655002000	CHECK VALVE/STRAINER-200 MESH CLEAN	5
11655003000	NOZZLE- 110" CLEANER	5
11655037000	FILTER-1/8" X 1/8" HOSE INLINE 200	1
11655038000	CHECK VALVE-1/8 X 1/8 INLINE SILICON	1
14100126000	BLADE-SQUEEGEE 60 DURO FLAT URETHANE	1
14100374000	FOAM- SQUEEGEE CLAMP	1
14100320000	WIPER- ABSORBANT SQUEEGEE (SPK)	1
11616025000	SWITCH-DUSTER CLOTH UP/DN LEVER TYPE	2
14100487000	SEAL - WASTE TANK, "D" SHAPE	1
11655024004	PREFILTER- OIL, SCREEN ONLY, CYL 40X30	1
14100390000	FOAM- MIDDLE FRAME SECTION	1
11655029001	FILTER- SPIN-ON OIL, 10 MICRON	1
11695010000	CASTER- 2" DUAL WHEEL	2
14100378000	FOAM- VACUUM DIFFUSER	1
11655034000	HOSE- 1.25ID, 24" LG, VACUUM	1
11603204000	HOSE CLAMP 3/4 TO 1 3/4 DIA, S.S.	1
11655035000	CUFF- HOSE CUFF, GREY VACUUM	1
14100607000	VACUUM HOUSING	1
14100606120	VACUUM BRUSHES- 120V (33384)	2
14900077000	OPERATIONS AND SERVICE GUIDE 1.6	1