

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



### 1. Identification

#### 1.1. Product identifier

**Product Identity** Ball Plug Pigment 321 Yellow 1-Pk  
**Alternate Names** Product Code: 160321YEL

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use** Color. Restricted to professional users.  
**Application Method** See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name** Brunswick Bowling Products, LLC  
525 W. Laketon Ave.  
Muskegon, MI 49441 USA

#### Emergency

**24 hour Emergency Telephone No. (CHEMTEL)** US: 800-255-3924  
International: +01-813-248-0585

**Customer Service: Brunswick Bowling Products, LLC** 231-725-4966

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Acute Tox. 5;H313	May be harmful in contact with skin. (Not adopted by US OSHA)
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
STOT SE 3;H335	May cause respiratory irritation.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



### Warning

H313 May be harmful in contact with skin.

**Safety Data Sheet**  
**Ball Plug Pigment 321 Yellow 1-Pk**

SDS Revision Date:

09/22/2015



- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H411 Toxic to aquatic life with long lasting effects.

**[Prevention]:**

- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.

**[Response]:**

- P302+352 IF ON SKIN: Wash with plenty of soap and water.
- P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P313 Get medical advice / attention.
- P321 Specific treatment (see information on this label).
- P333+313 If skin irritation or a rash occurs: Get medical advice / attention.
- P337+313 If eye irritation persists: Get medical advice / attention.
- P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P391 Collect spillage.

**[Storage]:**

- P403+233 Store in a well ventilated place. Keep container tightly closed.
- P405 Store locked up.

**[Disposal]:**

- P501 Dispose of contents / container in accordance with local / national regulations.

<b>3. Composition/information on ingredients</b>
--

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Tripropylene glycol diacrylate CAS Number: 0042978-66-5	75 - 100	Eye Irrit. 2;H319 STOT SE 3;H335 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]
Diglycidyl ether of bisphenol A CAS Number: 0025068-38-6	5 - 10	Eye Irrit. 2;H319 Skin Irrit. 2;H315 Skin Sens. 1;H317 Aquatic Chronic 2;H411	[1]
Alkyl(C12-C14)glycidyl ether CAS Number: 0068609-97-2	0.10 - 1.0	Skin Irrit. 2;H315 Skin Sens. 1;H317	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

<b>General</b>	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
<b>Inhalation</b>	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
<b>Eyes</b>	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	Rinse mouth with water and drink plenty of water.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Overview</b>	<b>Notes to Physician:</b> Treat Symptomatically  <b>Protection of First-Responders:</b> Avoid contact with skin, eyes and clothing. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; use artificial respiration with the aid of a pocket mask equipped with a one-way valve or other respiratory medical device.  See section 2 for further details.
<b>Inhalation</b>	May cause respiratory irritation.
<b>Eyes</b>	Causes serious eye irritation.
<b>Skin</b>	May be harmful in contact with skin. (Not adopted by US OSHA) May cause an allergic skin

**Safety Data Sheet**  
**Ball Plug Pigment 321 Yellow 1-Pk**

SDS Revision Date:

09/22/2015



reaction. Causes skin irritation.

**5. Fire-fighting measures**

**5.1. Extinguishing media**

Use extinguishing media appropriate to local circumstances and the surrounding environment.

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition: None known.

Avoid breathing dust / fume / gas / mist / vapors / spray.

**5.3. Advice for fire-fighters**

As in any fire, wear self-contained breathing apparatus in pressure-demand, MSHA/NIOSH approved or equivalent, and full protective gear.

**ERG Guide No.**            ----

**6. Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).

**6.2. Environmental precautions**

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

**6.3. Methods and material for containment and cleaning up**

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

**7. Handling and storage**

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



### 7.1. Precautions for safe handling

Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use.

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: None known.

Keep containers tightly closed in a dry, cool and well-ventilated place.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0025068-38-6	Diglycidyl ether of bisphenol A	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0042978-66-5	Tripropylene glycol diacrilate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0068609-97-2	Alkyl(C12-C14)glycidyl ether	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0025068-38-6	Diglycidyl ether of bisphenol A	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



0042978-66-5	Tripropylene glycol diacrylate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0068609-97-2	Alkyl(C12-C14)glycidyl ether	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

### 8.2. Exposure controls

- Respiratory** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
- Eyes** Safety glasses with side shields
- Skin** Chemical resistant gloves/gauntlets, boots and apron (where risk of splashing)
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

## 9. Physical and chemical properties

<b>Appearance</b>	Dark Blue Liquid
<b>Odor</b>	Slight solvent
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	Not Measured
<b>Flash Point</b>	> 232°C, > 450°F
<b>Evaporation rate (Ether = 1)</b>	Not Measured
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	Not Measured
<b>Specific Gravity</b>	Not Measured
<b>Solubility in Water</b>	Slight
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	1500 - 3000 cps
<b>Relative Density</b>	1.15 (H <sub>2</sub> O = 1); 10.07 lb/gal

**9.2. Other information**

No other relevant information.

### 10. Stability and reactivity

**10.1. Reactivity**

Hazardous Polymerization will not occur.

**10.2. Chemical stability**

Stable under normal circumstances.

**10.3. Possibility of hazardous reactions**

None under normal processing

**10.4. Conditions to avoid**

None known.

**10.5. Incompatible materials**

None known.

**10.6. Hazardous decomposition products**

None known.

### 11. Toxicological information

**Acute toxicity**

Based on the properties of the epoxy constituents and considering toxicological data on similar preparations this preparation may be an irritant and a skin and respiratory sensitizer. Low molecular weight epoxy constituents are irritating to eyes, mucous membranes and skin. Repeated skin contact may lead to irritation and sensitization, possibly with cross-sensitization to other epoxies. Skin contact with the preparation and exposure to spray mist and vapor should be avoided.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Tripropylene glycol diacrilate - (42978-66-5)	3,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Diglycidyl ether of bisphenol A - (25068-38-6)	> 5,000.00, Rat - Category: NA	20,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Alkyl(C12-C14)glycidyl ether - (68609-97-2)	No data	No data	No data	No data	No data

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



	available	available	available	available	available
--	-----------	-----------	-----------	-----------	-----------

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	3	May cause respiratory irritation.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Trippropylene glycol diacrilate - (42978-66-5)	4.50, Leuciscus idus	88.70, Daphnia magna	28.00 (72 hr), Scenedesmus subspicatus
Diglycidyl ether of bisphenol A - (25068-38-6)	3.10, Pimephales promelas	1.40, Daphnia magna	Not Available
Alkyl(C12-C14)glycidyl ether - (68609-97-2)	Not Available	Not Available	Not Available

### 12.2. Persistence and degradability



# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes; ( TRIPROPYLENE GLYCOL DIACRILATE ) <b>Note:</b> Per IMDG 2.10.2.7, not subject to marine pollutant provisions when inner containers of combination packaging less than 5 L (liquids) or 5 kg (solids)		
14.6. Special precautions for user	No further information		

## 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA )</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.

# Safety Data Sheet

## Ball Plug Pigment 321 Yellow 1-Pk

SDS Revision Date:

09/22/2015



**WHMIS Classification** D2B

**US EPA Tier II Hazards**

**Fire:** No

**Sudden Release of Pressure:** No

**Reactive:** No

**Immediate (Acute):** Yes

**Delayed (Chronic):** No

**EPCRA 311/312 Chemicals and RQs:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 302 Extremely Hazardous:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**EPCRA 313 Toxic Chemicals:**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Carcinogens (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Proposition 65 - Male Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**New Jersey RTK Substances (>1%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Pennsylvania RTK Substances (>1%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of

**Safety Data Sheet**  
**Ball Plug Pigment 321 Yellow 1-Pk**

SDS Revision Date:

09/22/2015



publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material in any process, unless specified in the text.

End of Document