CHAIN LUBE, 12OZ CAN

SDS Revision Date:

10/17/2019



# 1. Identification

1.1. Product identifier	
Product Identity	CHAIN LUBE, 12OZ CAN
Alternate Names	Item Number: G34205116000
1.2. Relevant identified uses of the substance or mixt	ure and uses advised against
Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.
1.3. Details of the supplier of the safety data sheet	
Company Name	Brunswick Bowling Products, LLC. 525 W. Laketon Ave.
	Muskegon, MI 49441 USA
Emergency	
24 hour Emergency Telephone No. (CHEMTEL)	US: 1-800-255-3924
Customer Service: Brunswick Bowling Products, LLC	International: +01-813-248-0585 231-725-4966

# 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Flam. Aerosol 1;H222	Extremely flammable aerosol.
Press. Gas;H280	Contains gas under pressure; may explode if heated.
Skin Irrit. 2;H315	Causes skin irritation.
Repr. 2;H361F	Suspected of damaging fertility.
STOT RE 2;H373	May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (Not Available)
Asp. Tox. 1;H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3;H412	Harmful to aquatic life with long lasting effects.
Simple Asphyxiant	May displace oxygen and cause rapid suffocation.

### 2.2. Label elements

CHAIN LUBE, 12OZ CAN

SDS Revision Date:

10/17/2019



Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

May displace oxygen and cause rapid suffocation.

### [Prevention]:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe mist / vapors / spray.

P264 Wash thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

### [Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P308+313 IF exposed or concerned: Get medical advice / attention.

P314 Get Medical advice / attention if you feel unwell.

P321 Specific treatment (see information on this label).

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice / attention.

P362 Take off contaminated clothing and wash before reuse.

CHAIN LUBE, 12OZ CAN

**SDS Revision Date:** 

10/17/2019



### [Storage]:

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122 °F.

### [Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified CAS Number: 0064742-52-5	25 - 50	Asp. Tox. 1;H304	[1]
Distillates (petroleum), solvent-refined heavy naphthenic; Baseoil-unspecified CAS Number: 0064741-96-4	10 - 25	Not Classified	[1]
Propane CAS Number: 0000074-98-6	10 - 25	Flam. Gas 1;H220 Press. Gas;H280	[1][2]
Butane CAS Number: 0000106-97-8	10 - 25	Flam. Gas 1;H220 Press. Gas;H280 Simple Asphyxiant	[1][2]
Hexane CAS Number: 0000110-54-3	5 - 10	Flam. Liq. 2;H225 Repr. 2;H361f Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 2;H411	[1][2]
Pentane, 2-methyl- CAS Number: 0000107-83-5	1 - 5	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 2;H411	[1]
Polybutene CAS Number: 0009003-29-6	1 - 5	Not Classified	[1]
Chlorinated paraffin c22-30 CAS Number: 0063449-39-8	1 - 5	Not Classified	[1]
METHYLPENTANE CAS Number: 0000096-14-0	1 - 5	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 2;H411	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been

CHAIN LUBE, 12OZ CAN

**SDS Revision Date:** 

10/17/2019



withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If victim is not breathing, or their breathing is irregular, or respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt, or waistband.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison control center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt, or waistband.
4.2. Most important sym	ptoms and effects, both acute and delayed
Overview	Symptoms of eye contact may include pain/irritation, watering, or redness.

Symptoms of eye contact may include pain/irritation, watering, or redness. Symptoms of inhalation may include respiratory tract irritation, coughing, nausea, vomiting, headache, drowsiness/fatigue, dizziness/vertigo, or unconsciousness. Symptoms of skin contact may include irritation or redness. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

CHAIN LUBE, 12OZ CAN

**SDS Revision Date:** 

10/17/2019



Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation Skin May be fatal if swallowed and enters airways.

### Causes skin irritation.

### 5. Fire-fighting measures

### 5.1. Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Do not breathe mist / vapors / spray.

### 5.3. Advice for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-plate operated in positive pressure mode.

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk without suitable training.

### ERG Guide No.

### 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

In a fire or if heated, a pressure increase will occur and the container may burst.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

In a fire or if heated, a pressure increase will occur and the container may burst.

For Non-Emergency Personnel: No action shall be taken involving any personal risk or without suitable training.

CHAIN LUBE, 12OZ CAN

**SDS Revision Date:** 

10/17/2019



Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

<u>For Emergency Responders</u>: If specialized clothing is required to deal with the spillage, take note of any information in section 10 on suitable and unsuitable materials.

<u>Environmental Precautions</u>: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil, or air).

<u>Small Spill:</u> Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large Spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements, or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material (e.g. sand, earth, vermiculite, or diatomaceous earth) and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

### 7. Handling and storage

### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool, and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Incompatible materials: Strong acids and oxidizing materials

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

### 8. Exposure controls and personal protection

### 8.1. Control parameters

### Exposure

CAS No.	Ingredient	Source	Value
0000074-98-6	Propane	OSHA	TWA 1000 ppm (1800 mg/m3)

CHAIN LUBE, 120Z CAN

SDS Revision Date:

10/17/2019



		ACGIH	Ensure Minimal Oxygen Content (ACGIH appendix F)
		NIOSH	TWA 1000 ppm (1800 mg/m3)
		Supplier	No Established Limit
0000096-14-0	METHYLPENTANE	OSHA	No Established Limit
		ACGIH	TWA: 500 ppm STEL: 1000 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000106-97-8	Butane	OSHA	No Established Limit
		ACGIH	TWA: 600 ppm STEL: 750 ppm
		NIOSH	TWA 800 ppm (1900 mg/m3)
		Supplier	No Established Limit
0000107-83-5	Pentane, 2-methyl-	OSHA	No Established Limit
		ACGIH	TWA: 500 ppm STEL: 1000 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0000110-54-3	Hexane	OSHA	TWA 500 ppm (1800 mg/m3)
		ACGIH	TWA: 20 ppm Skin
		NIOSH	TWA 50 ppm (180 mg/m3)
		Supplier	No Established Limit
0009003-29-6	Polybutene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0063449-39-8	Chlorinated paraffin c22-30	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064741-96-4	Distillates (petroleum), solvent-refined	OSHA	No Established Limit
	heavy naphthenic; Baseoil-unspecified	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-52-5	Distillates (petroleum), hydrotreated heavy	OSHA	No Established Limit
	naphthenic; Baseoil-unspecified	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

CHAIN LUBE, 120Z CAN

SDS Revision Date:

10/17/2019



8.2. Exposure controls	
Respiratory	Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eyes	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases, or dusts. If contact is possible, the following protection should be worn unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Chemical-resistant impervious gloves should be worn.
Engineering Controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.
See section 2 for further	details [Prevention]:

# 9. Physical and chemical properties

<b>A</b>	Linder avera di averal
Appearance	Unknown Liquid
Odor	Unknown
Odor threshold	Not determined
рН	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	>93.3 C (>199.9 F) Closed Cup
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Gas
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured
	Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	Not Measured
Solubility in Water	Not Measured

CHAIN LUBE, 12OZ CAN

**SDS Revision Date:** 

10/17/2019



Partition coefficient n-octanol/water (Log Kow)Not MeasuredAuto-ignition temperatureNot MeasuredDecomposition temperatureNot MeasuredViscosity (cSt)Kinematic (room temperature): <0.07 cm2/s (<7 cSt)</th>Relative Density0.879.2. Other informationUniversity (mineral oil component only)

### **10. Stability and reactivity**

10.1. Reactivity
Hazardous Polymerization will not occur.
10.2. Chemical stability
Stable under normal circumstances.
10.3. Possibility of hazardous reactions
No data available.
10.4. Conditions to avoid
Do not expose to heat or store at temperature above 120°F.
10.5. Incompatible materials
Strong acids and oxidizing materials
10.6. Hazardous decomposition products
Oxides of Carbon

### 11. Toxicological information

### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

# Safety Data Sheet CHAIN LUBE, 120Z CAN

SDS Revision Date:

10/17/2019



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Distillates (petroleum), solvent-refined heavy naphthenic;	No data	No data	No data	No data	No data
Baseoil-unspecified - (64741-96-4)	available	available	available	available	available
Propane - (74-98-6)	No data	No data	658.00, Rat -	No data	No data
	available	available	Category: NA	available	available
Butane - (106-97-8)	No data	No data	658.00, Rat -	No data	No data
	available	available	Category: NA	available	available
Hexane - (110-54-3)	25,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available	48,000.00, Rat - Category: NA
Pentane, 2-methyl (107-83-5)	No data	No data	No data	No data	No data
	available	available	available	available	available
Polybutene - (9003-29-6)	No data	No data	No data	No data	No data
	available	available	available	available	available
Chlorinated paraffin c22-30 - (63449-39-8)	11,700.00, Rat -	No data	No data	No data	No data
	Category: NA	available	available	available	available
METHYLPENTANE - (96-14-0)	No data	No data	No data	No data	No data
	available	available	available	available	available

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0000074-98-6	Propane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000096-14-0	METHYLPENTANE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000106-97-8	Butane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000107-83-5 Pentane, 2-methyl-		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000110-54-3	Hexane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0009003-29-6	03-29-6 Polybutene OSHA Select Carcinogen: No		Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

CHAIN LUBE, 12OZ CAN

**SDS Revision Date:** 

10/17/2019



0063449-39-8	Chlorinated paraffin c22-30 OS		Select Carcinogen: No
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064741-96-4	Distillates (petroleum), solvent-	OSHA	Select Carcinogen: No
refined heavy naphthenic; Baseoil- unspecified	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0064742-52-5 Distillates (petroleum),		OSHA	Select Carcinogen: No
hydrotreated heavy naphthenic; Baseoil-unspecified	NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity	2	Suspected of damaging fertility.
STOT-single exposure		Not Applicable
STOT-repeated exposure	2	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	1	May be fatal if swallowed and enters airways.

# **12. Ecological information**

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient 96 hr LC50 fish, 48 hr EC50 crustacea, ErC50 algae,
--

CHAIN LUBE, 12OZ CAN

SDS Revision Date:

10/17/2019



	mg/l	mg/l	mg/l
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil-unspecified - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Distillates (petroleum), solvent-refined heavy naphthenic; Baseoil-unspecified - (64741-96-4)	Not Available	Not Available	Not Available
Propane - (74-98-6)	Not Available	Not Available	Not Available
Butane - (106-97-8)	6.00, Fish (Piscis)	Not Available	Not Available
Hexane - (110-54-3)	2.50, Pimephales promelas	3,878.00, Daphnia magna	Not Available
Pentane, 2-methyl (107-83-5)	Not Available	Not Available	Not Available
Polybutene - (9003-29-6)	Not Available	Not Available	Not Available
Chlorinated paraffin c22-30 - (63449-39-8)	300.00, Lepomis macrochirus	102.00, Daphnia magna	Not Available
METHYLPENTANE - (96-14-0)	Not Available	Not Available	Not Available

#### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

#### 12.6. Other adverse effects

No data available.

### 13. Disposal considerations

#### 13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirement. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

CHAIN LUBE, 12OZ CAN

SDS Revision Date:

10/17/2019



### **14. Transport information**

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA	
14.1. UN number	UN1950	UN1950	Do Not Ship by Air	
14.2. UN proper shipping name	UN1950, Aerosols, 2.1, Limited Quantity	UN1950, Aerosols, 2.1, Limited Quantity		
14.3. Transport hazard class(es)	DOT Hazard Class: 2.1	<b>IMDG:</b> 2.1	Air Class:	
14.4. Packing group	Not Applicable	Not Applicable		
14.5. Environmental hazards				
IMDG N	larine Pollutant: No;			
14.6. Special precautions for user				
Ν	lo further information	EMS CODE: F-D S-U		

### 15. Regulatory information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.	
Toxic Substance Control Act ( TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.	
WHMIS Classification	A B1 D2A	
US EPA Tier II Hazards	Fire: Yes	
	Sudden Release of Pressure: Yes	
	Reactive: No	
	Immediate (Acute): Yes	

Delayed (Chronic): Yes

### EPCRA 311/312 Chemicals and RQs (lbs):

Hexane (5,000.00)

### EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### **EPCRA 313 Toxic Chemicals:**

Hexane

### Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

CHAIN LUBE, 12OZ CAN

SDS Revision Date:

10/17/2019



### **Proposition 65 - Developmental Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

#### **Proposition 65 - Female Repro Toxins (>0.0%):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### New Jersey RTK Substances (>1%):

	Butane	
	Hexane	
	Pentane, 2-methyl-	
	Propane	
Pennsylvania RTK Substances (>1%):		
	Butane	
	Hexane	
	METHYLPENTANE	
	Pentane, 2-methyl-	
	Propane	

### **16. Other information**

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

CHAIN LUBE, 12OZ CAN

SDS Revision Date:

10/17/2019



The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material in any process, unless specified in the text.

End of Document