SDS Revision Date: 11/10/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity DEFY Lane Conditioner

Alternate Names Product Part Number 62-860164-004 and 62-860164-001

Kit/Package Part Number: 62-860164-004 and 62-860164-001

Kit/Package Description: DEFY Lane Conditioner – 4 x 1 Gallon and 1 x 1 Gallon

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Lubricant. Restricted to professional users. Lane

Conditioner.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Brunswick Bowling Products, LLC.

525 W. Laketon Ave.

Muskegon, MI 49441. USA

Emergency

CHEMTREC (USA) (800) 424-9300

24 hour Emergency Telephone No. CHEMTEL 813-248-0585

Customer Service: Brunswick Bowling & Billiards 231-725-4966

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Skin Irrit. 3;H316 Causes mild skin irritation. (Not adopted by US OSHA)

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Warning

H316 Causes mild skin irritation.

[Prevention]:

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

[Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice / attention.

SDS Revision Date:

11/10/2014



[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 0064742-53-6	50 - 75	Asp. Tox. 1;H304	[1]
Mineral oil CAS Number: 0008042-47-5	10 - 25		[1]
Petroleum distillates, hydrotreated heavy naphthenic CAS Number: 0064742-52-5	1.0 - 10	Acute Tox. 4;H312	[1]
Poly(oxy-1,2-ethanediyl), .alpha[3,5- dimethyl -1-(2-methylpropyl)hexyl]omega hydroxy- CAS Number: 0060878-78-6	1.0 - 10	Skin Irrit. 2;H315 Eye Irrit. 2;H319	[1]
Mineral oil (saturated parrafin oil) CAS Number: 0008012-95-1	1.0 - 10		[1][2]

^[1] Substance classified with a health or environmental hazard.

4. First aid measures

4.1. Description of first aid measures

General No hazards which require special first aid measures. Do not breathe

dust/fume/gas/mist/vapors/spray. Repeated or prolonged skin contact may cause allergic

reactions with susceptible persons.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes **Eyes**

with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get

medical attention if any discomfort continues.

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a Skin

recognized skin cleanser.

Ingestion DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting

occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get

medical attention.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.
*The full texts of the phrases are shown in Section 16.

SDS Revision Date:

11/10/2014



4.2. Most important symptoms and effects, both acute and delayed

Overview

If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Skin

Causes mild skin irritation. (Not adopted by US OSHA)

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO_2 , powder, water spray. Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3. Advice for fire-fighters

In the event of fire, wear full protective clothing and NIOSH Approved Self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapors.

ERG Guide No. ----

SDS Revision Date:

11/10/2014



6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Pick up and transfer to properly labeled containers.

Caution - spillage may be slippery

Eliminate all sources of ignition in the vicinity of spilled material.

7. Handling and storage

7.1. Precautions for safe handling

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Storage Temperature: -50 - 50C (-58 - 122F)

For containers or container linings, use mild steel or high density polyethylene.

Do not use PVC.

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

SDS Revision Date:

11/10/2014



8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0008012-95-1 Mi	Mineral oil (saturated parrafin oil)	OSHA	TWA 5 mg/m3
		ACGIH	No Established Limit
		NIOSH	TWA 5 mg/m3 ST 10 mg/m3
		Supplier	No Established Limit
0008042-47-5	Mineral oil	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0060878-78-6	Poly(oxy-1,2-ethanediyl), .alpha[3,5-	OSHA	No Established Limit
dimethyl -1-(2-methylpropyl)hexyl]omega - hydroxy-		ACGIH	No Established Limit
	Hydroxy	NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-52-5 Petroleum distillates, hydrotreated heavy naphthenic	OSHA	No Established Limit	
	naphthenic	ACGIH	No Established Limit
	NIOSH	No Established Limit	
		Supplier	No Established Limit
	Distillates (petroleum), hydrotreated light naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m3 OSHA PEL and 10 mg/m3 ACGIH.

Carcinogen Data

CAS No.	Ingredient	Source	Value
0008012-95-1	Mineral oil (saturated parrafin oil)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008042-47-5	0008042-47-5 Mineral oil		Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Poly(oxy-1,2-ethanediyl), .alpha 3,5- dimethyl -1-(2- methylpropyl)hexyl]omega hydroxy-	OSHA	Select Carcinogen: No	
	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	

SDS Revision Date:

11/10/2014



0064742-52-5 Petroleum distillates, hydrotreated	OSHA	Select Carcinogen: No		
	heavy naphthenic	NTP	Known: No; Suspected: No	
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
0064742-53-6 Distillates (petroleum), hydrotreated light naphthenic	OSHA	Select Carcinogen: No		
	NTP	Known: No; Suspected: No		
	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		

8.2. Exposure controls

Respiratory Use NIOSH/MSHA approved respirator, following manufacturer's recommendations when

concentrations exceed permissible exposure limits.

Eyes Not required under normal conditions of use.

Skin Skin protection is not required under normal conditions of use. Oil impervious gloves and

oil impermeable apron recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

suitable respiratory protection must be worn.

Safety showers and eye wash stations should be provided in areas where this product is

used.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance Light brown Liquid
Odor Ocean Breeze
Odor threshold Not Measured
pH Not Measured
Melting point / freezing point Not Measured
Initial boiling point and boiling range Not Measured

Flash Point 137.2C/278.96F Tag Closed Cup

Evaporation rate (Ether = 1) Not Measured Flammability (solid, gas) Not Applicable

Upper/lower flammability or explosive limits Lower Explosive Limit: Not Measured

Upper Explosive Limit: Not Measured

Vapor pressure (Pa)Not MeasuredVapor DensityNot Measured

SDS Revision Date:

11/10/2014



Specific Gravity 0.852

Solubility in Water

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Decomposition temperature

Viscosity (cSt)

Not Measured

Not Measured

Not Measured

9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

10.6. Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

SDS Revision Date:

11/10/2014



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Mineral oil - (8042-47-5)	5,000.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Poly(oxy-1,2-ethanediyl), .alpha[3,5- dimethyl -1-(2-methylpropyl)hexyl]omega hydroxy (60878-78-6)	No data available	No data available	No data available	No data available	No data available
Mineral oil (saturated parrafin oil) - (8012-95-1)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

SDS Revision Date:

11/10/2014



12. Ecological information

12.1. Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	Not Available	Not Available	Not Available
Mineral oil - (8042-47-5)	10.00, Lepomis macrochirus	Not Available	Not Available
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Poly(oxy-1,2-ethanediyl), .alpha[3,5- dimethyl -1-(2-methylpropyl)hexyl]omega hydroxy (60878-78-6)	Not Available	Not Available	Not Available
Mineral oil (saturated parrafin oil) - (8012-95-1)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

12.3. Bioaccumulative potential

Contains components with the potential to bioaccumulate.

12.4. Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

SDS Revision Date: 11/10/2014



14. Transport information

DOT (Domestic Surface

Transportation)

14.1. UN number14.2. UN proper shipping

name

14.3. Transport hazard

class(es)

Not Applicable Not Regulated

DOT Hazard Class: Not

Applicable **DOT Label:** ---

14.4. Packing group Not Applicable

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

IMO / IMDG (Ocean ICAO/IATA

Transportation)

Not Applicable

Not Regulated Not Regulated
Not Regulated Not Regulated

IMDG: Not Applicable

Sub Class: Not Applicable

able

Not Applicable

Air Class: Not Applicable

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

WHMIS Classification Not Regulated

US EPA Tier II Hazards Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous:

(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:

(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):

(No Product Ingredients Listed)

SDS Revision Date:

11/10/2014



Proposition 65 - Female Repro Toxins (>0.0%):

(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):

(No Product Ingredients Listed)

N.J. RTK Substances (>1%):

Mineral oil (saturated parrafin oil)

Penn RTK Substances (>1%):

Mineral oil (saturated parrafin oil)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H304 May be fatal if swallowed and enters airways.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material in any process, unless specified in the text.

End of Document