

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### 1. Identification

#### 1.1. Product identifier

**Product Identity**

Logic Lane Conditioner

**Alternate Names**

Kit/ Package Part Number: 62-860162-001 and 62-860162-005

Kit/Package Description: Logic Lane Conditioner - 1 X 1 5 quart

and 4 x 5 quart Container

Product Part Number: 62-860162-001 and 62-860162-005

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

Lubricant. Restricted to professional users. Lane Conditioner.

**Application Method**

See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

Brunswick Bowling Products, LLC.

525 W. Laketon Ave.

Muskegon, MI 49441. USA

**Emergency**

**CHEMTREC (USA)**

(800) 424-9300

**24 hour Emergency Telephone No.**

CHEMTEL 813-248-0585

**Customer Service: Brunswick Bowling & Billiards**

231-725-4966

### 2. Hazard(s) identification

#### 2.1. Classification of the substance or mixture

Skin Irrit. 3;H316

Causes mild skin irritation. (Not adopted by US OSHA)

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

### Warning

H316 Causes mild skin irritation.

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### [Prevention]:

P260 Do not breathe mist / vapors / spray.  
P262 Do not get in eyes, on skin, or on clothing.

### [Response]:

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.  
P331 Do NOT induce vomiting.  
P332+313 If skin irritation occurs: Get medical advice / attention.

### [Storage]:

No GHS storage statements

### [Disposal]:

No GHS disposal statements

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Distillates (petroleum), hydrotreated light naphthenic CAS Number: 0064742-53-6	25 - 50	Asp. Tox. 1;H304	[1]
Mineral oil CAS Number: 0008042-47-5	25 - 50	Asp. Tox. 1;H304	[1]
Distillates (petroleum), hydrotreated middle CAS Number: 0064742-46-7	1.0 - 10	Asp. Tox. 1;H304 Skin Irrit. 2;H315	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



**Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

**Ingestion** DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Skin** Causes mild skin irritation. (Not adopted by US OSHA)

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Do not use: water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

### 5.3. Advice for fire-fighters

None

ERG Guide No. ----

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Local authorities should be advised if significant spillages cannot be contained.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closeable containers.

This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.

Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Keep at temperatures between 0 C and 50 C. Keep Containers tightly closed in a dry, cool and well ventilated place.

For containers or container linings, use mild steel or high density polyethylene.

Do not use PVC.

Incompatible materials: Strong oxidizing agents and acids.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

No data available.

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
0008042-47-5	Mineral oil	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-46-7	Distillates (petroleum), hydrotreated middle	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup> OSHA PEL and 10 mg/m<sup>3</sup> ACGIH.

##### Carcinogen Data

CAS No.	Ingredient	Source	Value
0008042-47-5	Mineral oil	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-46-7	Distillates (petroleum), hydrotreated middle	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

#### 8.2. Exposure controls

##### Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

##### Eyes

Protective safety glasses recommended

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



- Skin** Skin protection is not required under normal conditions of use. Oil impervious gloves and oil impermeable apron recommended.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.
- See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

<b>Appearance</b>	Light yellow Liquid
<b>Odor</b>	Citrus
<b>Odor threshold</b>	Not Measured
<b>pH</b>	No information available
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	No information available
<b>Flash Point</b>	Flash Point 137.2 C / 279 F (Tag Closed Cup)
<b>Evaporation rate (Ether = 1)</b>	No information available
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> No information available <b>Upper Explosive Limit:</b> No information available
<b>Vapor pressure (Pa)</b>	No data available
<b>Vapor Density</b>	No data available
<b>Specific Gravity</b>	0.852
<b>Solubility in Water</b>	Not Measured
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	No information available
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Less than 2000 cps

#### 9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Excessive heat and open flame.

#### 10.5. Incompatible materials

Strong oxidizing agents and acids.

#### 10.6. Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

### 11. Toxicological information

#### Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available
Mineral oil - (8042-47-5)	5,000.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Distillates (petroleum), hydrotreated middle - (64742-46-7)	> 5,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation. (Not adopted by US OSHA)
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/l (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	Not Available	Not Available	Not Available
Mineral oil - (8042-47-5)	Not Available	Not Available	Not Available
Distillates (petroleum), hydrotreated middle - (64742-46-7)	54.00, <i>Jordanella floridae</i>	68.00, <i>Daphnia magna</i>	Not Available

### 12.2. Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.



# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### 12.3. Bioaccumulative potential

Contains components with the potential to bioaccumulate.

### 12.4. Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

	<b>DOT (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>14.1. UN number</b>	Not Applicable	Not Regulated	Not Regulated
<b>14.2. UN proper shipping name</b>	Not Regulated	Not Regulated	Not Regulated
<b>14.3. Transport hazard class(es)</b>	<b>DOT Hazard Class:</b> Not Applicable	<b>IMDG:</b> Not Applicable <b>Sub Class:</b> Not Applicable	<b>Air Class:</b> Not Applicable
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: No		
<b>14.6. Special precautions for user</b>	No further information		

## 15. Regulatory information

<b>Regulatory Overview</b>	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
<b>Toxic Substance Control Act ( TSCA)</b>	All components of this material are either listed or exempt from listing on the TSCA Inventory.
<b>WHMIS Classification</b>	Not Regulated

# Safety Data Sheet

## Logic Lane Conditioner

SDS Revision Date:

03/09/2015



### US EPA Tier II Hazards

Fire: No

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes

Delayed (Chronic): No

### EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### New Jersey RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

### Pennsylvania RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

**Safety Data Sheet**  
**Logic Lane Conditioner**

SDS Revision Date:

03/09/2015



**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material in any process, unless specified in the text.

End of Document