

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



1. Identification

1.1. Product identifier

Product Identity 62-860062-000 Pinsetter Grey Touch up Paint

Alternate Names Pinsetter Gray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Brunswick Bowling Products, LLC
525 W. Laketon Ave.
Muskegon, MI 49441 USA

Emergency

24 hour Emergency Telephone No. (CHEMTEL) US: 1-800-255-3924
International: +01-813-248-0585

Customer Service: Brunswick Bowling Products, LLC 231-725-4966

2. Hazard(s) identification

2.1. Classification of the substance or mixture

| | |
|--------------------|--|
| Flam. Gas 1;H220 | Extremely flammable gas. |
| Press. Gas;H280 | Contains gas under pressure; may explode if heated. |
| Acute Tox. 4;H332 | Harmful if inhaled. |
| Skin Irrit. 2;H315 | Causes skin irritation. |
| Eye Irrit. 2;H319 | Causes serious eye irritation. |
| Repr. 2;H361D | Suspected of damaging the unborn child. |
| STOT SE 3;H336 | May cause drowsiness or dizziness. |
| STOT RE 2;H373 | May cause damage to organs through prolonged or repeated exposure. Specific Target Organs: (hearing organs) |
| Simple Asphyxiant | May displace oxygen and cause rapid suffocation. |

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

Safety Data Sheet
62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness and dizziness.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
May displace oxygen and cause rapid suffocation.

[Prevention]:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves / eye protection / face protection.

[Response]:

P302+352 IF ON SKIN: Wash with plenty of soap and water.
P304+312 IF INHALED: Call a POISON CENTER or doctor / physician if you feel unwell.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
P308+313 IF exposed or concerned: Get medical advice / attention.
P314 Get Medical advice / attention if you feel unwell.
P321 Specific treatment (see information on this label).
P332+313 If skin irritation occurs: Get medical advice / attention.
P337+313 If eye irritation persists: Get medical advice / attention.
P340 Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P362 Take off contaminated clothing and wash before reuse.
P377 Leaking gas fire - do not extinguish unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.
P405 Store locked up.
P410 Protect from sunlight.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|---|----------|--|--------|
| Acetone CAS Number: Proprietary | 25 - 50 | Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336 | [1][2] |
| Propane CAS Number: 0000074-98-6 | 10 - 25 | Flam. Gas 1;H220 Press. Gas;H280 | [1][2] |
| Xylene CAS Number: 0001330-20-7 | 10 - 25 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 | [1][2] |
| Butane CAS Number: 0000106-97-8 | 1.0 - 10 | Flam. Gas 1;H220 Press. Gas;H280 Simple Asphyxiant | [1][2] |
| Propylene glycol monomethyl ether acetate CAS Number: 0000108-65-6 | 1.0 - 10 | Flam. Liq. 3;H226 | [1] |
| Ethyl Benzene CAS Number: 0000100-41-4 | 1.0 - 10 | Flam. Liq. 2;H225 Acute Tox. 4;H332 STOT RE 2;H373 Asp. Tox. 1;H304 | [1][2] |
| Toluene CAS Number: 0000108-88-3 | 1.0 - 10 | Flam. Liq. 2;H225 Repr. 2;H361d Asp. Tox. 1;H304 STOT RE 2;H373 Skin Irrit. 2;H315 STOT SE 3;H336 | [1][2] |
| Titanium dioxide CAS Number: 0013463-67-7 | 1.0 - 10 | Not Classified | [1][2] |

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



4. First aid measures

4.1. Description of first aid measures

| | |
|-------------------|---|
| General | In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. |
| Inhalation | Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth. |
| Eyes | Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention. |
| Skin | Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser. |
| Ingestion | If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------|--|
| Overview | <p>Inhalation: May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful</p> <p>Skin Contact Causes skin irritation.</p> <p>Eye Contact: Causes serious eye irritation.</p> <p>Ingestion: Expected to be a low ingestion hazard.</p> <p>Symptoms related to the physical, chemical and toxicological characteristics: Headache. May cause drowsiness and dizziness. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.</p> <p>Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.</p> |
| Inhalation | Harmful if inhaled. May cause drowsiness or dizziness. |
| Eyes | Causes serious eye irritation. |
| Skin | Causes skin irritation. |

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



5. Fire-fighting measures

5.1. Extinguishing media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Do not use water jet as an extinguisher, as this will spread the fire.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor.

Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



6.3. Methods and material for containment and cleaning up

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

Incompatible materials: Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



8. Exposure controls and personal protection

8.1. Control parameters

Exposure

| CAS No. | Ingredient | Source | Value |
|--------------|---|----------|--|
| Proprietary | Acetone | OSHA | TWA 1000 ppm (2400 mg/m ³) STEL 2400 mg/m ³ |
| | | ACGIH | TWA: 500 ppm STEL: 750 ppm |
| | | NIOSH | 250 ppm (590 mg/m ³) TWA |
| | | Supplier | No Established Limit |
| 0000074-98-6 | Propane | OSHA | TWA 1000 ppm (1800 mg/m ³) |
| | | ACGIH | Ensure Minimal Oxygen Content (ACGIH appendix F) |
| | | NIOSH | TWA 1000 ppm (1800 mg/m ³) |
| | | Supplier | No Established Limit |
| 0000100-41-4 | Ethyl Benzene | OSHA | TWA 100 ppm (435 mg/m ³) STEL 125 ppm |
| | | ACGIH | TWA: 20 ppm ^{2B} , Revised 2011, |
| | | NIOSH | TWA 100 ppm (435 mg/m ³) ST 125 ppm (545 mg/m ³) |
| | | Supplier | No Established Limit |
| 0000106-97-8 | Butane | OSHA | No Established Limit |
| | | ACGIH | TWA: 600 ppm STEL: 750 ppm |
| | | NIOSH | TWA 800 ppm (1900 mg/m ³) |
| | | Supplier | No Established Limit |
| 0000108-65-6 | Propylene glycol monomethyl ether acetate | OSHA | No Established Limit |
| | | ACGIH | TWA: 50 ppm STEL: 75 ppm |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0000108-88-3 | Toluene | OSHA | TWA 200 ppm C 300 ppm 500 ppm (10-minute maximum peak) STEL 150 ppm |
| | | ACGIH | TWA: 20 ppm R |
| | | NIOSH | TWA 100 ppm (375 mg/m ³) ST 150 ppm (560 mg/m ³) |
| | | Supplier | No Established Limit |
| 0001330-20-7 | Xylene | OSHA | STEL 150 ppm |
| | | ACGIH | TWA: 100 ppm STEL: 150 ppm |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| 0013463-67-7 | Titanium dioxide | OSHA | TWA 15 mg/m ³ |
| | | ACGIH | TWA: 10 mg/m ³ ^{2B} , Revised 2006, |
| | | NIOSH | Footnote ca |
| | | Supplier | No Established Limit |

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|--------------|---|--------|---|
| Proprietary | Acetone | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000074-98-6 | Propane | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000100-41-4 | Ethyl Benzene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0000106-97-8 | Butane | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000108-65-6 | Propylene glycol monomethyl ether acetate | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0000108-88-3 | Toluene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0001330-20-7 | Xylene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0013463-67-7 | Titanium dioxide | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |

8.2. Exposure controls

- Respiratory** If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator
- Eyes** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.
- Skin** **Hands:** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier
Other: Wear appropriate chemical resistant clothing.
- Engineering Controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Other Work Practices **Thermal hazards:** Wear appropriate thermal protective clothing, when necessary. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

| | |
|--|---|
| Appearance | Unknown Liquified Gas |
| Odor | Unknown |
| Odor threshold | Not determined |
| pH | Not Measured |
| Melting point / freezing point | -305.68 F (-187.6 C) |
| Initial boiling point and boiling range | -43.78F (-42.1 C) |
| Flash Point | -156.0 F (-104.4 C) |
| Evaporation rate (Ether = 1) | Not Measured |
| Flammability (solid, gas) | Gas |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 1.9% Upper Explosive Limit: 12.8% |
| Vapor pressure (Pa) | 2421.92 hPa estimated |
| Vapor Density | Not Measured |
| Specific Gravity | 0.78 |
| Solubility in Water | Not Measured |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured |
| Auto-ignition temperature | 550F (287.78 C) |
| Decomposition temperature | Not Measured |
| Viscosity (cSt) | Not Measured |
| VOC Content | 534.243453 g/l Regulatory |
| Density | 6.49 lbs/gal |
| % Volatile | 80.52% |

9.2. Other information

No other relevant information.

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials

Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Fluorine. Chlorine.

10.6. Hazardous decomposition products

Oxides of Carbon

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

2-butoxyethanol and its acetate are readily absorbed through the skin and will cause harmful effects on the blood.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|-------------------------|---------------------------------|---|---------------------------------------|---|--------------------------------|
| Acetone - (Proprietary) | 5,800.00, Rat - Category: NA | 7,426.00, Guinea Pig - Category: NA | 76.00, Rat - Category: NA | 50.10, Rat - Category: NA | No data available |
| Propane - (74-98-6) | No data available | No data available | 658.00, Rat - Category: NA | No data available | No data available |
| Xylene - (1330-20-7) | 4,299.00, Rat - Category: 5 | 1,548.00, Rabbit - Category: 4 | No data available | 20.00, Rat - Category: NA | 5,000.00, Rat - Category: 4 |
| Butane - (106-97-8) | No data available | No data available | 658.00, Rat - Category: NA | No data available | No data available |

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



| | | | | | |
|--|-------------------------------|----------------------------------|--------------------------|--------------------------|------------------------------|
| Propylene glycol monomethyl ether acetate - (108-65-6) | 8,532.00, Rat - Category: NA | 5,000.00, Rabbit - Category: 5 | No data available | No data available | 4,345.00, Rat - Category: NA |
| Ethyl Benzene - (100-41-4) | 3,500.00, Rat - Category: 5 | 15,433.00, Rabbit - Category: NA | 17.20, Rat - Category: 4 | No data available | 4,000.00, Rat - Category: NA |
| Toluene - (108-88-3) | 636.00, Rat - Category: 4 | 8,400.00, Rabbit - Category: NA | No data available | No data available | No data available |
| Titanium dioxide - (13463-67-7) | 10,000.00, Rat - Category: NA | 10,000.00, Rabbit - Category: NA | No data available | 6.82, Rat - Category: NA | No data available |

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Classification | Category | Hazard Description |
|-------------------------------|----------|--|
| Acute toxicity (oral) | --- | Not Applicable |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | 4 | Harmful if inhaled. |
| Skin corrosion/irritation | 2 | Causes skin irritation. |
| Serious eye damage/irritation | 2 | Causes serious eye irritation. |
| Respiratory sensitization | --- | Not Applicable |
| Skin sensitization | --- | Not Applicable |
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | --- | Not Applicable |
| Reproductive toxicity | 2 | Suspected of damaging the unborn child. |
| STOT-single exposure | 3 | May cause drowsiness or dizziness. |
| STOT-single exposure | --- | Not Applicable |
| STOT-repeated exposure | 2 | May cause damage to organs through prolonged or repeated exposure. |
| Aspiration hazard | --- | Not Applicable |

12. Ecological information

12.1. Toxicity

Toxic to aquatic life

49.72% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 49.72% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, | 48 hr EC50 crustacea, | ErC50 algae, |
|------------|------------------|-----------------------|--------------|
|------------|------------------|-----------------------|--------------|

Safety Data Sheet

62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



| | mg/l | mg/l | mg/l |
|--|-----------------------------|--------------------------|---|
| Acetone - (Proprietary) | 100.00, Pimephales promelas | 10.00, Daphnia magna | 20.565 (72 hr), Ulva pertusa |
| Propane - (74-98-6) | Not Available | Not Available | Not Available |
| Xylene - (1330-20-7) | 3.30, Oncorhynchus mykiss | 8.50, Palaemonetes pugio | 100.00 (72 hr), Chlorococcales |
| Butane - (106-97-8) | 6.00, Fish (Piscis) | Not Available | Not Available |
| Propylene glycol monomethyl ether acetate - (108-65-6) | 100.00, Salmo gairdneri | 500.00, Daphnia magna | Not Available |
| Ethyl Benzene - (100-41-4) | 4.20, Oncorhynchus mykiss | 2.93, Daphnia magna | 3.60 (96 hr), Pseudokirchneriella subcapitata |
| Toluene - (108-88-3) | 5.80, Oncorhynchus mykiss | 19.60, Daphnia magna | Not Available |
| Titanium dioxide - (13463-67-7) | Not Available | Not Available | Not Available |

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

ACETONE -0.24
 ETHYLBENZENE 3.15
 N-BUTANE 2.89
 PROPANE 2.36
 TOLUENE 2.73
 XYLENE 3.12 - 3.2

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

13.1. Waste treatment methods

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Safety Data Sheet
62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

| | DOT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA |
|---|--|--|--------------------|
| 14.1. UN number | UN1950 | Do not ship by ocean | Do not ship by air |
| 14.2. UN proper shipping name | UN1950, Aerosols, 2.1, Limited Quantity | | |
| 14.3. Transport hazard class(es) | DOT Hazard Class: 2.1 | IMDG: | Air Class: |
| 14.4. Packing group | Not Applicable | Not Applicable | Not Applicable |
| 14.5. Environmental hazards | | | |
| IMDG | Marine Pollutant: No | | |
| 14.6. Special precautions for user | No further information | | |

15. Regulatory information

| | |
|--|---|
| Regulatory Overview | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. |
| Toxic Substance Control Act (TSCA) | All components of this material are either listed or exempt from listing on the TSCA Inventory. |
| WHMIS Classification | A B1 D2A |

US EPA Tier II Hazards

Fire: Yes
Sudden Release of Pressure: Yes
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): Yes

EPCRA 311/312 Chemicals and RQs (lbs):

Acetone (5,000.00)
Ethyl Benzene (1,000.00)
Toluene (1,000.00)
Xylene (100.00)

Safety Data Sheet
62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethyl Benzene

Toluene

Xylene

Proposition 65 - Carcinogens (>0.0%):

Carbon black

Ethyl Benzene

Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

Toluene

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Acetone

Butane

Ethyl Benzene

Propane

Titanium dioxide

Toluene

Xylene

Pennsylvania RTK Substances (>1%):

Acetone

Butane

Ethyl Benzene

Propane

Titanium dioxide

Toluene

Xylene

16. Other information

Safety Data Sheet
62-860062-000 Pinsetter Grey Touch up Paint

SDS Revision Date:

07/28/2015



The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material in any process, unless specified in the text.

End of Document