Information Sheet

ATTACK ZONE MRTM

Part Number

60-102931

Specifications


Blue & Red Pearl

Mica Reactive coverstock

Polished Finish

Hook Potential: 17.5 - 9.5 (dull/shiny)

Typical Length: 6 Typical Backend: 10 RG Max: 2.703 RG Min: 2.662 Diff. RG: 0.041 Average RG: 7.2 Track Flare: 8.1




Reaction Characteristics

Attack Zone MR[™] features a two-color reactive reactive coverstock with "mica" additive and an all-new high differential, three-piece puck augmented core to further enhance ball performance at the promational price point. Attack Zone MR[™] features the highest hook potential and back end reaction of any ball in its class.

The Attack Zone MR[™] is perfect for medium to dry lane conditions and the entire spectrum of bowler styles.


Notes on Drilling

Note: The Attack Zone MR's high differential three piece puck augmented high performance puddle core are marked by a riser pin. All weights of the **Attack Zone** line can be drilled using the techniques developed for two-piece balls. See Brunswick's "Seven Popular Layouts" for detailed drilling information.




Brunswick SEVEN POPULAR LAYOUTS


MAXIMUM TRACK FLARE HIGH REACTIVITY 1-Leverage Pin with 9" hole




2-Leverage Pin-heavy spot toward grip center




3-Leverage Pin with Axis hole




4-Positive label shift




5-Pin between Axis and Leverage



7-Negative label shift



6-Axis Pin with 9" hole



MINIMUM TRACK FLARE LOW REACTIVITY



$$(H) = Heavy Spot$$



