



# ALL THE RIGHT ELEMENTS.

©2012 Brunswick Bowling & Billiards Corporation. Item# 10-093300-085 • Form #0512-03D

**NEXUS**  
f(P+S)

**Brunswick**  
BowlwithBrunswick.com

# NEXXUS™ *f*(P+S)



## ADDAPTIVE *f*(P+S) PEARL COVERSTOCK

The **Addaptive *f*(P+S) Pearl** coverstock is Brunswick's hottest innovation in performance enhancing additive chemistry. *f*(P+S) describes our newest formula that combines our new (P)rojection and our new (S)nap additives together to create our most aggressive pearl coverstock to date. The Projection additive easily pushes the super aggressive coverstock down lane where the Snap additive connects with the lane for an extraordinary backend hook motion. Being able to combine multiple additives in a coverstock allows Brunswick to effectively fine tune the length, mid-lane and backend characteristics of the ball.

## CORE

The **Nexus Arrowhead** core features a single density squared-off elliptical inner core that is dynamically designed to stay on line, enhancing downlane projection. This long and sleek core helps the **Nexxxus *f*(P+S)** preserve revs and ball speed into the backend of the lane which results in increased pin action and higher scores.

## BALL MOTION

The **Nexxxus *f*(P+S)** is our strongest snapping pearl ball to date and extends the limits of our Ball Comparison chart. With its High Gloss finish, the **Nexxxus *f*(P+S)** offers our highest breakpoint shape potential & most continuation of any Brunswick ball to date.

With an extraordinary ball motion the **Nexxxus *f*(P+S)** skids easily through the front, saves axis rotation in the mid-lane and grabs the backend for unbelievable snap on medium to heavy oil lane conditions.

## REACTION SETUP

The **Nexxxus *f*(P+S)** can be drilled using the standard drilling techniques developed for asymmetric bowling balls.

## LIGHTWEIGHT ENGINEERING

At Brunswick, the unique core shape of each individual ball is used for weights from 14 to 16 pounds. This approach to lightweight ball engineering provides bowlers with consistent ball reaction characteristics across this weight range. At 12 and 13 pounds, Brunswick uses a generic core shape with a RG-differential that is close enough to the 14 to 16 pound shape so the same drilling instructions can be used.



## SPECIFICATIONS

Hook Potential	Low(10)	<input type="text" value="185"/>	High(200)
Length	Early(25)	<input type="text" value="120"/>	Long(235)
Breakpoint Shape	Smooth Arc(10)	<input type="text" value="105"/>	Angular(105)
RG Differential	Low(0)	<input type="text" value="0.056"/>	High(.060)
RG Average	Center Heavy(1)	<input type="text" value="3.8"/>	Cover Heavy(10)

- Nexus Arrowhead Core
- Addaptive *f*(P+S) Pearl Coverstock
- 2- Color, Bronze and Graphite Pearl
- Hardness: 73-75
- 500 Siaair Micro Pad; Rough Buff Finish
- Chart Position: V-1
- Part No. 60-105471-93X



16 LB      15 LB      14 LB      13 LB      12 LB

<b>RG-MAX</b>	2.546	2.558	2.575	2.632	2.655
<b>RG-INT</b>	2.534	2.546	2.593	2.621	2.644
<b>RG-MIN</b>	2.490	2.502	2.519	2.589	2.612
<b>RG-DIFF</b>	0.056	0.056	0.056	0.043	0.043
<b>RG-ASY</b>	0.012	0.012	0.012	0.011	0.011

